

SUCTION HOSE

Northline Lightweight PVC Flexible Suction Hose is top quality hose supplied by Goodyear. The Suction Hose sizes range from 2 1/2" to 6". Our Aluminum couplings are made from extruded 6061-T6 lightweight aluminum alloy. Threaded couplings are finished black anodized and laser engraved with a clear understanding of the thread type and size being provided. All swivels are attached using roller bearings and are supplied as long handle style.

With the most advanced collar attachment in the industry, Northline's Suction hose is far superior to others in the industry. The collar is made from durable lightweight plastic, molded four inches wide. With the length of the shank on the coupling, inserted into the hose and the width of the collar combined, the chance of leakage is minimal when the hose is flexed while in use.



Standard Lengths and sizes as follows:

FSH-9682-000 2 1/2" x 10 ft. Male x Female Threaded Couplings

FSH-9682-100 3" x 10 ft. Male x Female Threaded Couplings

FSH-9682-200 4" x 10 ft. Male x Female Threaded Couplings

FSH-9682-300 4 1/2" x 10 ft. Male x Female Threaded Couplings

FSH-9682-400 5" x 10 ft. Male x Female Threaded Couplings

FSH-9682-500 6" x 10 ft. Male x Female Threaded Couplings

All sizes are available at non-standard lengths and can be supplied with Storz Fittings, Double Female Threads and Cam-Lock Fittings.

The Flexible PVC hose is 50% lighter than conventional rubber hose used in water suction applications. It remains flexible at temperatures from 15°F to 150°F (-9°C to 65°C). The smooth bore provides a high rate of flow even under bending conditions. This lightweight hose is exceptionally flexible and easy to handle. The hose can flex 90 degrees without kinking. The rigid helix resists crushing and will not collapse under rated vacuum. Maximum operating pressure is 35 PSI.

for more information email cheryl@classafire.com